

HATHORN H5

CAMERA SYSTEM



Get A Quote

PROUDLY DESIGNED AND MANUFACTURED IN NORTH AMERICA

**DESIGNED
SPECIALLY FOR
THE TOOL RENTAL
INDUSTRY**



Screen Shot
Function



Daylight
Readable Display



200 ft of
Push Rod



Self-Levelling
Camera Heads



Record to
USB



512Hz High
Power Sonde



Works with 18V
Milwaukee® or
Equivalent
Batteries



Industry-Leading
Warranty

The Hathorn® H5 has been specially designed for the rental industry with ruggedness and simplicity in mind. The H5 comes with a metal-guarded 5.5" daylight readable shatter resistant LCD monitor with 1,000 cd/m² of brightness, making it the brightest monitor in the rental industry. It offers USB video recording with a screen shot feature allowing the user to record MPEG4 video and JPEGs to a portable USB drive.

The H5 is a complete system with your choice of rugged Hathorn camera heads and three different stiffnesses of push rod. These systems are compatible with 18V Milwaukee® (or equivalent) batteries for ultimate portability and over 5 hours of runtime on a single charge. Portability is never an issue with the H5 as these lightweight units are only 45lbs.

All H5s feature a footage counter and a 512Hz sonde. All Hathorn products are North American made with butt-welded steel frame construction and feature military-grade faceplates and connectors.

Hathorn products have been trusted by rental centers across the country for over a decade to deliver strong return on investment and unmatched durability.



HATHORN
INSPECTION CAMERAS

North America 1-866-HATHORN

International 1-905-604-7040

hathorncorp.com | sales@hathorncorp.com

HATHORN H5

CAMERA SYSTEM

PROUDLY DESIGNED AND MANUFACTURED IN NORTH AMERICA

Specifications

Display

Size & Type	5.5" (14 cm) impact-resistant, daylight-readable LCD
Resolution & Brightness	1024 x 600 pixels with 1,000 cd/m2

Recording, Storage & Features

Recording Options	MPEG4 video (H.264 at 30 fps) & JPEG screenshot
Storage Options	USB
USB Capacity	USB 2.0 up to 32Gb
Hard Drive Capacity	Does not include a hard drive
Menu Languages	English, Spanish, French
Footage Counter	Feet or meters - resettable
Sonde Frequencies	High power 512Hz
Push Rod	200 ft. of HDPE push rod with coax core

Power

Battery (not incl.)	Only Milwaukee® M18 18V or equivalent
Battery Life	~5Hrs. using 3.0Ah
Battery Extender	Auto dimming & auto saving
AC/DC Adapter	12V - 4.1A (included)

Weight & Dimensions

Weight without Battery	45lb (20.4Kg)
Dimensions (L x W x H)	19" x 15.5" x 29.5" (48cm x 39cm x 75cm)

Environmental

Water Resistance	IP65
Operating Temperature	14°F to 122°F (-10°C to 50°C)
Storage Temperature	-4°F to 140°F (-20°C to 60°C)



Catalog #	Camera Head	Self Levelling	Rod Length	Rod Size	Min. 90° Elbow	Max Pipe Well Lit
H5-2168-SL	1.68"	✓	200 ft.	1/2"	3"	12"
H5-2143-SL	1.43"	✓	200 ft.	1/2"	3"	10"
H5-2123-SL	1.23"	✓	200 ft.	0.400" or 3/8"	2"	6"
H5-2100	1"	✗	200 ft.	3/8"	1.5"	4"

*Straight View Cameras Available